

The background of the entire page is a soft-focus image of numerous overlapping spheres. Some spheres are a vibrant green, while others are a pale, almost white color. They are scattered across the frame, creating a sense of depth and movement. The lighting is bright and even, highlighting the smooth, reflective surfaces of the spheres.

SEPURAN[®] N₂
Product overview

OUR CLASSIC PRODUCTS



	4" Short Module	4" Module	4" Cartridge
Material of construction			
Cast in place/not replaceable	SS304	SS304	SS304
Pr/T rating			
Pressure	≤ 16 barg / ≤ 232 psig	≤ 16 barg / ≤ 232 psig	≤ 20 barg / ≤ 290 psig
Temperature	1-70 °C / 33.8 - 158 °F	1-70 °C / 33.8 - 158 °F	1-70 °C / 33.8 - 158 °F
Minimum capacity			
7 barg / 95% / 25 °C	11.3 Nm ³ /h	20.6 Nm ³ /h	20.6 Nm ³ /h
	423 scfh	769 scfh	769 scfh
Air factor	2.1	2.1	2.1
9 barg / 95% / 55 °C	17.9 Nm ³ /h	32.5 Nm ³ /h	32.5 Nm ³ /h
	668 scfh	1213 scfh	1213 scfh
Air factor	2.4	2.4	2.4
Nominal dimensions – diameter x length			
	114.3 x 873 mm	114.3 x 1339 mm	108.7 x 1237 mm
	4.5 x 34.4"	4.5 x 52.7"	4.3 x 48.7"
Thread			
Type	NPT	NPT or BSPP	
Feed and retentate	0.5"	0.5"	
Permeate	1.5"	1.5"	
Weight			
	10 kg / 22 lbs	13 kg / 28.7 lbs	8.3 kg / 18.36 lbs

SEPURAN® N₂ General information



Housing	6" Cartridge	Housing	6" Long Cartridge	Long Housing
SS316	Al	SS316	Al	SS316
	≤ 25 barg / ≤ 362 psig		≤ 25 barg / ≤ 362 psig	
	1-70 °C / 33.8 - 158 °F		1-70 °C / 33.8 - 158 °F	
	45.3 Nm ³ /h		65.5 Nm ³ /h	
	1691 scfh		2444 scfh	
	2.1		2.1	
	71.5 Nm ³ /h		103.4 Nm ³ /h	
	2669 scfh		3858 scfh	
	2.4		2.4	
124 x 1292 mm	154.8 x 1310 mm	168.3 x 1448 mm	154.8 x 1860 mm	168.3 x 1998±25 mm
4.88 x 50.9"	6.1 x 51.6"	6.6 x 57.0"	6.1 x 73.2"	6.6 x 78.7±1"
BSPP		NPT		NPT
0.75"		1.0"		1.5"
1.5"		2.0"		2.0"
13 kg / 28.66 lbs	8.3 kg / 18.3 lbs	27 kg / 59.5 lbs	9.3 kg / 20.5 lbs	33.7 kg / 74.3 lbs

This information and all technical and other advice are based on Evonik's present knowledge and experience. However, Evonik assumes no liability for such information or advice, including the extent to which such information or advice may relate to third party intellectual property rights. Evonik reserves the right to make any changes to information or advice at any time, without prior or subsequent notice.

EVONIK DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, AND SHALL HAVE NO LIABILITY FOR, MERCHANTABILITY OF THE PRODUCT OR ITS FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE), OR OTHERWISE. EVONIK SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND.

It is the customer's sole responsibility to arrange for inspection and testing of all products by qualified experts. Reference to trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used.

° = registered trademark

Evonik Fibres GmbH

Gewerbepark 4
4861 Schörfling
Austria

PHONE +43 7662 6006-2891
sepuran@evonik.com

www.sepuran.com
www.evonik.com

02/EU